


CUBE DOCK

2ch Fast Charger



Battery Model	98W	160W ~ 390W
LED Color	Orange(3.0A)	Red(6.0A)

GENTREE Batteries and Chargers are communicate for optimized charge

1. Orange = 3.5A Charge / Red = 6A Charge / GREEN = Full
2. Please reattach if Led color is different with table above

LED	State	Error type	Error Causes
RED	Blink	Inner Part failure	Failure of SMPS or Etc
GREEN	Blink	Channel Disable	Battery Sleep mode or Etc
OFF		Main Power Failure	Main power(AC) Failure

Guide



1 Switch On after plug AC cable



2 Attach battery pack in horizon softly

! GENTREE battery and charger communicate for charge optimizing
E/N CUBE, MONSTER : Max 6.0A
G CUBE 98W, BUMBLEBEE and 3rd party batteries : MAX 3.0A



3 LED indicates state of charge.

RED LED : 6A
ORANGE LED : 3A
GREEN LED Lighting: Full charged

Error Code

- GREEN LED All Lighting : Channel Diactived by Battery Sleep mode or Etc
- LED Off : Main power(AC) Failure

Safety

● Read Before Use

! Danger

- * Do not disassemble its housing arbitrary. It could cause accidents.
- * Avoid Humid and Hot Environments.
- * Recommended using with GENTREE Battery packs.
(Communication is supported only GENTREE Battery packs.)
- * Must use AC cables have earth connector.
- * Do not short (+) and (-).
- * Only charge Li-ion 16.8V(4SxP) battery

! Warning

- * Do not block air duct. It could cause malfunction.
- * Avoid moisture.
- * Guarantee is expired when disassemble arbitrary it.

Guarantee

✔ Product Guarantee

- * 2 years free repair is guaranteed for manufacturer faulty
- * Contact to dealer or manufacturer for asking guarantee policy and Repairment
(TEL : 032-556-8940 / KAKAO : gentree / nddman@gentree.co.kr)

💰 Contents Guarantee

- * Losing save of shooting and works by malfunction of products is not compensatable.

Specification

G - C062	
Channel	All Channels charged with Max Performance in simultaneous
Performance	6.0A Charge : E/N CUBE, MONSTER 3.0A Charge : G CUBE 98W, BUMBLEBEE, Others
Rated AC Input	Volt. 100 ~ 240V / Cur. Max 4A / 50~60Hz
Charge Voltage	DC 16.8V Max
Consumption	Max 250W
Charge Time	98W : Approx. 3H 20m (3.0A) 145W : Approx. 4H 20m (3.0A) 160W : Approx. 3H 20m (6.0A) 195W : Approx. 3H 50m (6.0A) 290W : Approx. 4H 50m (6.0A) 390W : Approx. 6H 30m (6.0A)
Recommend Temp.	-10°C ~ 40°C
Dimension(W x H x D)	230 x 91 x 211 mm
Weight	Approx. 2.2 Kg

Dimension (Unit:mm)

